

Multifarm 75

Multifarm 90

ENGINE		PERKINS	PERKINS
Direct Injection Perkins Diesel Engine		1104D-44 +Tier 2	1104D-44T +Tier 3
Rated Power (ISO) kW		51	61
Rated Speed (rpm)		2200	2200
Max. Torque (Nm)		273	352
Max. Torque Speed (rpm)		1400	1400
Bore/Stroke		105/127	105/127
Displacement/No of Cylinders (cm³)		4400/4	4400/4T
Compression Ratio		18.2:1	19.3:1
Water Cooling		STD	STD
Air Filter		STD	STD
Tank Capacity (lt)		75	75
CLUTCH			
Independent Dual Dry Clutch (inch)		12	12
Mechanical Engagement		STD	STD
TRANSMISSION			
Basic Transmission 12 Fwd + 12 Rev		STD	STD
Mechanical Reverse Shuttle		STD	STD
Rear Mechanical Diff. Lock		STD	STD
POWER TAKE OFF			
Mechanical Engagement		STD	STD
Ground Speed 540/540E (rpm)		STD	STD
1" 3/8 (34,9 mm) PTO Shaft with 6 Splines		STD	STD
4WD FRONT AXLE			
Mechanical 4WD Engagement		STD	STD
4 WD Max. Steering Angle (°)		55	55
2WD Max. Steering Angle (°)		56	56
BRAKING SYSTEM			
Mechanical Oil-bath Graphite Coated Rear Brakes - 10 Discs		STD	STD
HYDRAULIC SYSTEM+HITCH			
Mechanical Operated		STD	STD
Control Functions: Position, Draft, Intermix and Floating		STD	STD
Max. Lifting Power (kg)		2700	2700
Hydraulic Pump Steering Delivery (ltr/min)		53+28	53+28
CAT II 3-Point Linkage		STD	STD
Standard Auxiliary Valves (1STD+1Float)		2	2
TYRES, WHEELS & DIMENSIONS			
Front Tyres	2WD	750-16	750-16
Front Tyres	4WD	360/70 R20	360/70 R20
Rear Tyres	2WD	420/70 R30	420/70 R30
Rear Tyres	4WD	420/70 R30	420/70 R30
Front Track Adjustment	4WD (mm) #	1554-1812	1554-1812
Rear Track Adjustment	(mm) #	1224-1932	1224-1932
Total Length with Ballast	(mm)	3743	3743
Max Ground Clearance	(mm)	367	367
Height to ROPS	(mm)	2441	2441
Minimum Turning Radius with Brakes 4WD (mm)		2400	2400
Weight 2WD Without Ballast 4WD (kg)		2710	2710
Weight 4WD Without Ballast (kg)		2860	2860
CONFIGURATION			
Front Ballast Weights 36kg Each 2WD/4WD		6 x STD	6 x STD
Rear Ballast of 45kg Each		2 x STD	4 x STD

STD = Standard - = Not Available OPT = Optional

= Track adjustment not with listed tyres

*See operations and maintenance manual for adjustment with specific tyres.

Whilst every effort is made to ensure that the specifications, descriptions and illustrations in this brochure are correct at the time of print these are also subject to change without notice.

MULTIFARM



MULTIFARM

75•90

Landini®

Passion for Innovation.