

SERIES 2



SERIES 2

2-050

Landini[®]

Passion for Innovation.

ENGINE		YANMAR
Type		4TNV88-KLAN
Rated Power (ISO) kW		35
Rated speed (rpm)		2800
Max. Torque (Nm)		141
Max. Torque Speed (rpm)		1200
Bore/Stroke		88x90
Displacement/No of Cylinders (cm³)		2189/4
Water Cooling		STD
Air Filter		Dry
Tank Capacity (lt)		40
CLUTCH		
Independent Dual Dry Clutch (inch)		9
Mechanical Engagement		STD
TRANSMISSION		
Basic Gearbox + Reverse Shuttle 12Fwd + 12Rev		STD
Rear Mechanical Diff. Lock		STD
POWER TAKE OFF		
Mechanical Engagement		STD
2 Speeds 540/750 (rpm)		STD
1" 3/8 PTO Shaft with 6 Splines		STD
Ground Speed		STD
4WD FRONT AXLE		
Mechanical 4WD Engagement		STD
Max. steering angle		55°
BRAKING SYSTEM		
Mechanical		STD
Oil-bath Graphite Coated Rear Brakes - 6 Discs		STD
HYDRAULIC SYSTEM & HITCH		
Mechanical operated.		STD
Position, Draft, Intermix & Floating Control Functions		STD
Standard Lifting Capacity (kg)		1200
Hydraulic Pump Delivery, Hydraulic Lift/Steering (ltr/min)		28/20
3-Point Linkage, CAT I		STD
Auxiliary Hydraulic Valves Double Acting		2
TYRES, WHEELS & DIMENSIONS		
Front Tyres	4WD	260/70 R16
Rear Tyres	4WD	320/70 R24
Total Length with Ballast	(mm)	3225
Max Ground Clearance	(mm)	385
Wheelbase 4WD	(mm)	1760
Height at Steering Wheel	(mm)	1312
Min Width	(mm)	1383
Height to Safety Frame	(mm)	2097
Weight without Ballast 4WD	(kg)	1460
Front Ballast Weights	(kg)	4x24
TRACK #		
Front Track Adjustment 4WD (mm) #		1083-1314
Rear Track Adjustment (mm) #		872-1258
CONFIGURATION		
Platform		Standard

Whilst every effort is made to ensure that the specifications, descriptions and illustrations in this brochure are correct at the time of print these are also subject to change without notice.