

# Landini



SUPER SERIES 7865 | 8865

### ENGINE

Direct Injection Perkins Diesel Engine	1104C-44	1104C-44
Rated Power (ISO) kW	55	60
Rated Speed (rpm)	2200	2200
Max. Torque (Nm)	290	294
Max. Torque Speed (rpm)	1400	1400
Bore/Stroke	105/127	105/127
Displacement/No of Cylinders (cm <sup>3</sup> )	4400/4	4400/4
Water Cooling	STD	STD
Air Filter	STD	STD
Tank Capacity (lt)	86	86

### CLUTCH

Independent Dual Dry Clutch (inch)	12	12
Coating	Cerametalic	Cerametalic
Mechanical Engagement	STD	STD

### TRANSMISSION

Basic Gearbox + Reverse Shuttle 12Fwd + 12Rev	STD	STD
Rear Mechanical Diff. Lock	STD	STD

### POWER TAKE OFF

Mechanical Engagement	STD	STD
2 Speeds 540/1000 (rpm)	STD	STD
1" 3/8 PTO Shaft with 6 Splines	STD	STD
Synchronised with Gearbox	STD	STD

### 4WD FRONT AXLE

Double-Action Direction Ram Cylinder	STD	STD
Epicyclic Final Drives	STD	STD
Mechanical 4WD Engagement	STD	STD
Max. Steering Angle 55°	STD	STD

### BRAKES

Mechanical	STD	STD
Oil-bath Graphite Coated Rear Brakes - 10 Discs	STD	STD

### HYDRAULIC POWER LIFT

Mechanical Operated	STD	STD
Position, Draft, Intermix & Floating Control Functions	STD	STD
Standard Lifting Capacity	2700	2700
Max Operating Pressure (bar)	180	180
Hydraulic Pump Delivery (ltr/min)	53	53
3-Point Linkage, CAT II	STD	STD
Auxiliary Hydraulic Valves	2	2

### WEIGHTS & DIMENSIONS (IN RUNNING ORDER)

Front Tyres 2WD	7.50-16	9.00-16
Front Tyres 4WD	320/70R24	12.4R24
Rear Tyres 4WD	16.9R30	18.4R30
Total Length without Ballast (mm)	3810	3810
Max Ground Clearance (mm)	430	430
Wheelbase 2WD/4WD (mm)	2340/2316	2340/2316
Height at Steering Wheel (mm)	1720	1720
Height Over Bonnet (mm)	1454	1488
Min Width (mm)	1870	1870
Height to Safety Frame (mm)	2590	2590
Minimum Turning Radius without Brakes 4WD (mm)	4100	4100
Minimum Turning Radius with Brakes 4WD (mm)	3600	3600
Weight without Ballast 4WD (kg)	3147	3147

### TRACK #

Front Track Adjustment 4WD (mm) #	1352-1856	1500-2048
Rear Track Adjustment (mm) #	1400-2000	1400-2000

### OPTIONAL EQUIPMENT

Front Ballast Weights 36 kg each	6 x 36	8 x 36
Rear Ballast Weights 60 kg each	2 x 60	4 x 60

**STD** = Standard

**OPT** = Optional

**-** = Not Available

**#** = Track adjustments not with listed tyres.

See operations and maintenance manual for adjustment with specific tyres.

Whilst every effort is made to ensure that the specifications, descriptions and illustrations in this brochure are correct at the time of print these are also subject to change without notice.

