

# Landini



POWERFARM 90 | 100 | 110

# SPECIFICATION

90

100

110

## ENGINE

Direct Injection Perkins Diesel Engine	1104D-44T	1104D-44TA	1104D-44TA
Rated Power (ISO) kW	61	68	75
Rated Speed (rpm)	2200	2200	2200
Max. Torque (Nm)	345	393	416
Max. Torque Speed (rpm)	1400	1400	1400
Bore/Stroke	105/127	105/127	105/127
Displacement/No of Cylinders (cm <sup>3</sup> )	4400/4	4400/4	4400/4
Water Cooling	STD	STD	STD
Air Filter Dry Type	STD	STD	STD
Tank Capacity (lt)	120	120	120

## CLUTCH

Mechanical Engagement, Independent	STD	STD	STD
Dual Dry Clutch (inch)	12	12	12

## TRANSMISSION

Speed Four with Mechanical Shuttle 12Fwd + 12Rev	STD	STD	STD
--	-----	-----	-----

## POWER TAKE OFF

Mechanical Engagement	STD	STD	STD
2 Speeds 540/1000 (rpm) with Ground Speed	STD	STD	STD

## 4WD FRONT AXLE

Double-acting Steering Cylinder, Epicyclic Reduction in Hubs	STD	STD	STD
4WD Mechanical Engagement	STD	STD	STD
Max. Steering Angle (°)	55	55	55
Twin Lock Electro-hydraulic Diff Lock	STD	STD	STD

## BRAKES

Hydraulic Control Oil-bath Graphite Coated Rear Brakes - 10 discs	STD	STD	STD
Oil-bath Graphite Coated Front Brakes - 4 Discs (4WD Only)	STD	STD	STD
IBS Integrated Braking System (4WD Only)	STD	STD	STD
Hydraulic Trailer Brake	OPT	OPT	OPT

## HYDRAULIC POWER LIFT

Mechanical Operated	STD	STD	STD
Position, Draft, Intermix and Floating Control Functions	STD	STD	STD
Standard Lifting Capacity	2600	—	—
Standard Lifting Power with 2 Additional Auxiliary Cylinders (kg)	—	3700	4200
Hydraulic Pump Delivery (ltr/min)	53	53	53
CAT III 3-Point Linkage	STD	STD	STD
Standard Auxiliary Hydraulic Valves	2	2	2

## WEIGHTS & DIMENSIONS

Total Length without Ballast (mm)	4136	4136	4160
Max Ground Clearance 2WD/4WD (mm) #	465-325	465-325	440-340
Wheelbase 2WD/4WD (mm)	2341/2316	2341/2316	2365/2340
Height at Steering Wheel (mm)	1790	1790	1790
Min Width (mm)	1732	1732	1760
Height to ROPS (mm)	2560	2560	2560
Minimum Turning Radius without Brakes 4WD (mm)	4100	4100	4100
Max. Weight without Ballast 4WD (kgs)	3600	3600	3650

## TRACK #

Front Track Adjustment 4WD (mm) #	1456-1938	1456-1938	1456-1938
Rear Track Adjustment (mm) #	1292-2012	1292-2012	1292-2012

## TYRES & WHEELS

Front 2WD	900 x 16	900 x 16	900 x 16
Front 4WD	13.6R24	380/70R24	14.9R24
Rear 2WD & 4WD	16.9R34	480/70R34	18.4R34

## OPERATORS LAYOUT

Analog Control Panel - Programmable	STD	STD	STD
Silent Block mounted Platform and Cab	STD	STD	STD

## BALLAST

Front Ballast Weights (kg) 2WD/4WD	7x36	7x36	7x36
Rear Ballast Weights (kg) 2WD/4WD	2x60	4x60	4x60

## OPTIONAL EQUIPMENT

Cab and Air Conditioner	OPT	OPT	OPT
-------------------------	-----	-----	-----

See operations and maintenance manual for adjustment with specific tyres.

Whilst every effort is made to ensure that the specifications, descriptions and illustrations in this brochure are correct at the time of print these are also subject to change without notice.

**STD** = Standard    **-** = Not Available  
**OPT** = Optional    **#** = Track adjustments not with listed tyres.



**ARGO Industrial (Pty) Ltd.**

www.argosa.co.za • landini@argosa.co.za