

Landini



SOLETS 60N | 75N | 90N

SPECIFICATION

SOILS 60N
SOILS 75N
SOILS 90N

| ENGINE | | | |
|--|--------------------------------|-------------------------|-------------------------|
| Model | 4100FL | 4100FLT | 4105ELT |
| Type | Water Cooled, Direct Injection | Turbo Charged | Turbo Charged |
| Max. Power ISO kW | 44 | 55 | 65 |
| No. of Cylinders | 4 | 4 | 4 |
| Rated Engine rpm | 2200 | 2200 | 2200 |
| Torque (Nm) | 230 | 289 | 339 |
| Air Cleaner | Dry Air Cleaner | Dry Air Cleaner | Dry Air Cleaner |
| Fuel Tank Capacity | 73 | 73 | 73 |
| CLUTCH | | | |
| Type | Double Clutch | Double Clutch | Double Clutch |
| | Independent PTO Lever | Independent PTO Lever | Independent PTO Lever |
| Plate Size (inch/mm) | 12/310 | 12/310 | 12/310 |
| TRANSMISSION | | | |
| Type | Synchromesh 12Fwd+12Rev | Synchromesh 12Fwd+12Rev | Synchromesh 12Fwd+12Rev |
| Speed (km/h) | Min. 0.50 - Max. 31.07 | Min. 0.51 - Max. 31.1 | Min. 0.51 - Max. 31.1 |
| POWER TAKE OFF | | | |
| Mechanical Engagement | STD | STD | STD |
| Speed | 540/540E | 540/540E | 540/540E |
| Ground speed PTO | STD | STD | STD |
| No. of Splines | 6 | 6 | 6 |
| BRAKING SYSTEM | | | |
| Type | Oil Immersed Brakes | Oil Immersed Brakes | Oil Immersed Brakes |
| Parking Brakes | Independent | Independent | Independent |
| HYDRAULIC SYSTEM | | | |
| Position, Draft, Mix Control | STD | STD | STD |
| Lifting Capacity (kg) | 2500 | 2500 | 2500 |
| 3-Point Linkage | CAT II | CAT II | CAT II |
| Two Double Acting Remote Valves | STD | STD | STD |
| Hydraulic Oil Flow (lt/min @ Rated Engine rpm) | 48 | 48 | 48 |
| Steering Oil Flow (lt/min @ Rated Engine rpm) | 26 | 26 | 26 |
| STEERING | | | |
| Type | Power Steering | Power Steering | Power Steering |
| ELECTRICAL | | | |
| Type | 12V | 12V | 12V |
| TYRES, WHEELS & DIMENSIONS | | | |
| Overall Length (mm) | 4150 | 4150 | 4150 |
| Overall Width (mm) | 1475 | 1475 | 1475 |
| Overall Height with ROPS (mm) | 2350-2700 | 2350-2700 | 2350-2700 |
| Wheelbase (mm) | 2216 | 2216 | 2216 |
| Minimum Ground Clearance (mm) | 250-300 | 250-300 | 250-300 |
| Front Tyres 2WD | 600-16 | 600-16 | 600-16 |
| Front Tyres 4WD | 260/10 R16 | 8-18 | 8-18 |
| Rear Tyres 2WD & 4WD | 360/70 R24 | 14.9-24 | 14.9-24 |
| CONFIGURATION | | | |
| Platform | STD | STD | STD |
| Cab with Airconditioning | OPT | OPT | OPT |

STD = Standard - = Not Available **OPT** = Optional

Whilst every effort is made to ensure that the specifications, descriptions and illustrations in this brochure are correct at the time of print these are also subject to change without notice.