SOLIS



SOLIS

Part Hall

Passion for Innovation.

Solis 45

ENGINE		
LINGINE		
Max. Power (kW)	35kW	
Rated Speed (rpm)	2100rpm	
Max. Torque (Nm)	176	
Max. Torque Speed (rpm)	1200	
Bore/Stroke (mm)	100/118	
Displacement (cc) / No. of Cylinders	2780/3	
Туре	Water cooled	
Air Cleaner:Dry Air Filter	STD	
Engine Oil Capacity (It)	8,2	
Fuel Tank Capacity (It)	55	
CLUTCH		
Type & Size (mm)	Dual pedal postition/280mm	
TRANSMISSION		
Type / Fwd & Rev Gears	Constant Mech 8+2	
POWER TAKE OFF		
PTO (rpm)	540	
BRAKING SYSTEM		
Service Brake - Oil Immersed Brakes	STD	
Parking Brake	Hand Mechanical	
Turning Radius with Brake (m)	3,2	
Turning Radius without Brake (m)	3,89	
HYDRAULIC SYSTEM		
Standard Lifting Power (kg)	1200 at ball ends	
Hydraulic Lift Oil Flow (lt/min @ rated eng. rpm)	23I/min	
TYRES, WHEELS & DIMENSIONS		
Overall Length (mm)	3820	
Overall Width (mm)	1790	
Overall Height (mm)	1840	
Wheelbase (mm)	1980	
Minimum Ground Clearance (mm)	441	
Standard Front Track Width (mm)	1310	
Standard Front Track Adjustable (mm)	-	
Standard Rear Track Width (mm)	1460	
Standard Rear Track Adjustable (mm)	-	
Front Tyres	600x16	
Rear Tyres	12,4x28	
Weight (Unballasted) (kg)	2445	

4 x 29kg

STD = Standard - = Not Available OPT = Optional

Whilst every effort is made to ensure that the specifications, descriptions and illustrations in this brochure are correct at the time of print these are also subject to change without notice.



Front Weight