

TREKKER3



TREKKER3 COMPACT / COMPACT S

3-085

Landini

Passion for Innovation.

ENGLISH		TREKKER 3-085 COMPACT		TREKKER 3-085 COMPACT S	
ENGINE					
Manufacturer		Kohler			
Model		KDI 2504 TCR			
Max power (ISO)		hp/kW	75 / 55		
Max torque		Nm	315		
Displacement		cm³	2500		
Cylinders / valves		4 TA / 16			
Emissions category		Stage V			
CAPACITIES					
Fuel tank		l	45		
TRANSMISSION					
Type		Speed Four			
No. of gears FWD+REV		16+8 w/creeper			
Transmission control		Manually operated - 11" independent dry clutch			
Reverse shuttle		Mechanical			
Transmission oil cooler		●			
REAR PTO					
Type		Servoassisted dry clutch			
Speeds		rpm	540 / 540E		
Rotation - spline shaft type		Clockwise (rear view) - 1-3/8" PTO shaft with 6 splines			
STEERING AND BRAKING SYSTEM					
Steering system		Hydrostatic Hi-Drive			
Steering control		Single lever operating left/right independent clutches and brakes			
Braking system		Hydrostatic wet multidisc graphite brakes			
HYDRAULIC SYSTEM					
Circuit type - pump type		Open center - twin pump			
Flow rate hitch & remotes + steering		l/min	50 + 30		
Max operating pressure		bar	180		
Rear remote valves		● 2 ○ 3 / 3+1 w/flow selector			
REAR HYDRAULIC HITCH					
Type		Mechanical with position/draft/intermix/floating control			
Category - coupler type		● Cat.1 / Cat.2 - fixed ball ends			
Max lift capacity at hitch points		kg	2600		
DRIVING POSITION					
Platform type		ROPS w/central tunnel w/side gears and reverse shuttle commands			
Platform suspension		Suspended on hydro-silentblocks			
Halogen lights		Halogen driving and working lights			
Beacon light		○			
ON-BOARD TECHNOLOGY					
Digital dashboard		●			
WEIGHT AND DIMENSIONS					
Wheelbase		mm	1350		
Ground clearance		mm	220		
Min-max height over ROPS		mm	2200 (2486 w/top beacon light)		
Min length without front weights		mm	3050		
Min-max overall width		mm	1260-1290 (metallic) / 1280 (rubber)	1150	
Shipping weight		kg	3250	3150	
Front weight support		Structural			
Front weights		kg	○ 2x30 / 4x30		
TRACKS					
Bottom track carrier rollers		4 sealed and lubricated			
Top track carrier roller		Sealed and permanently lubricated			
Track tension adjustment system		Hydraulic track tension adjuster with permanently lubricated sprocket gear			
Front suspension		Leaf spring			
Rear suspension		Crossbar on independent track frames			
Track shoe type		● Metal ○ Rubber		● Metal	
Track shoe width		mm	280 - 310 (metallic) / 300 (rubber)	250 (metallic)	
Track width		mm	980	900	

Key: ● standard ○ option

All data and illustrations provided in this brochure are for information purposes only and can be changed without notice.