SUPER



SUPER

90 • 100 • 110 • 120



Passion for Innovation.

ENGLISH		SUPER 90	SUPER 100	SUPER 110	SUPER 120
ENGINE					
Rated power (97/68/EC - ISO TR 14396)	hp/kW	82 / 60	93 / 68	102 / 75	111 / 81
Rated engine speed (rpm)			2	2200	
Max torque at 1400 rpm(Nm)		352	393	416	416
Manufacturer		Perkins			
Emission Stage - without after-treatment system		Tier3			
Cylinders / Displacement / Valves			4/4	.4 I / 8V	
Air Filtration		Powercore			
Air intake system		Turbo Turbo aftercooled			
Fuel injection system / Filtration system		Direct injection - Fuel filter with pre-filter / Fuel filter with water separator			
CAPACITIES					
Fuel tank	L		!	95	
TRANSMISSION					
Type			Mechanical /	Electrohydraulic	
No. of gears - std		12 FWD + 12 REV with Synchro Shuttle			
No. of gears - opt		12 FWD + 12 REV w/RPS with Modulation control & De-clutch			
Creeper		Opt			
Minimum speed with creeper	m/h	340			
Engine speed at 30 km/h	rpm	2200			
FRONT AND REAR AXLES	ТРПП	2200			
Front axle	I		4WD w/o Hvd	ralock w/o brakes	
Traction type		4WD			
Front differential lock	Optional	Hydralock full locking differential (4WD)			
Rear differential lock	Ориона	Mechanical			
REAR PTO		IVIECTIALIICAI			
			Mac	chanical	
Type Speeds	rom	540/1000 Std -540/540E Opt			
Ground speed PTO	rpm			Std	
BRAKING SYSTEM				3iu	
Front braking system		w/o Front brakes			
Rear braking system		Oil Bath Graphite Coated			
HYDRAULIC SYSTEM			Oli Bath Gra	prille Coaled	
	au rata (LDM)		E4.24/C.m.eh.r.e.e	h+ a\	
Hydraulic pump for rear hitch & remote valves + steering - flow rate (LPM) Rear remote valves - type, flow rate, number		54+24 (Synchro shuttle) - 54+30 (RPS) 2 Standard - 3 Opt			
Free flow return		Z Standard - 5 Opt Std			
				510	
REAR 3-POINT HITCH			D.4	January I.	
Rear hitch control		Mechanical			
Category -coupler type		II - Fixed balls ends std - Quick-hitch hooks opt			
Ergonomic Lift System (E.L.S.)		Opt 5080			
Max lifting capacity at hitch points with assist cylinders	kg	45	20	50	180
CAB / PLATFORM				0.1	
Platform configuration		Std			
Total View Slim cab mounted on silent blocks			Std		
In-cab noise level	dB(A)	83			
Cab heating / Climate control system		Heat and ventilation - Air conditioned Cab			
Mechanical seat		Std			
Comfort pneumatic seat			Opt		
WEIGHTS AND DIMENSIONS					
Wheelbase	mm		316		40
Max height over FOPS/cab without beacon lights	mm	26	25		70
Shipping weight - measured with average specs	kg	3450			
Gross vehicle weight	kg	5350			
Rear tyre size		480/70R34			
Front tyre size		380/70R24			
Front Nose weights	Qty / Kg	7 x 36			
Rear wheel weights	Qty / Kg	2 x 60 (Per Wheel)			
near wheel weights	QIY Ng	Z X 00 (FEI WHEEL)			

